




## ECHELON MAX EM-B400 Series

### Ultra Low Loss Phase Stable Cable Assemblies, SMA 18GHz

#### Features

- VSWR 1.35:1 Max up to 18GHz
- SMA Connectors both ends
- 83% Phase Velocity
- Double Shielded
- Shielding Effectivity 90dB
- 4.0 mm FEP Outer Jacket, Gray
- EM-B400 Series Ultra Low Loss
- Phase and Amplitude Stable



ELECTRICAL SPECIFICATION (25° C, sea level)				
Description	Min	Typ	Max	Units/Note
Impedance		50Ω		Ohm
Frequency	DC		18	GHz
VSWR, 18GHz			1.35:1	@18GHz
Velocity of Propagation		83		%
Dielectric Withstand		1000		Volts
RF Shielding	90			dB
Capacitance		80		pF/m
Temperature	-55		165	° C
Phase change vs bending		±0.3		° /GHz
Phase change vs temperature		750		PPM, (-45 - 85 ° C)

Performance by Frequency (Cable Only)		
Frequency (MHz)	Insertion Loss(25° C) dB/ft	Average Power(25° C @ Sea Level) Watts
1000	0.10	510
2000	0.14	420
3000	0.18	362
4000	0.21	310
6000	0.25	255
8000	0.27	220
10000	0.33	197
15000	0.40	162
18000	0.44	146

Contact us:  
 sales@echelon-mw.com  
[www.echelon-mw.com](http://www.echelon-mw.com)  
 770.742.8847



## *ECHELON MAX EM-B400 Series*

### Ultra Low Loss Phase Stable Cable Assemblies, SMA 18GHz

MECHANICAL SPECIFICATION, CONNECTORS		
Description	Connector 1	Connector 2
Type	SMA Male Straight/Right Angle	SMA Female
Interface Spec	MIL-STD-348	MIL-STD-348
Mating Cycles	500	500
Hex Wrench Size	5/16 in	N/A
Mating Torque	8-10in-lbs/0.9-1.13nm	8-10in-lbs/0.9-1.13nm
Material	Stainless Steel	Stainless Steel
Pin/Receptacle	Gold Plated BeCu	Gold Plated BeCu
Dielectric Type	PTFE	PTFE

MECHANICAL SPECIFICATION, CABLE	
Description	Specification
Cable Type	EM-B400
Diameter	0.157in. (4.0mm)
Weight	0.024lb/ft(0.036kg/m)
Minimum Bend Radius, Static	0.787in. (20mm)
Minimum Bend Radius, Dynamic	1.587in. (40mm)
Length Tolerance	±0.196in(±5mm)


Contact us:  
 sales@echelon-mw.com  
[www.echelon-mw.com](http://www.echelon-mw.com)  
 770.742.8847



## ECHELON MAX EM-B400 Series

### Ultra Low Loss Phase Stable Cable Assemblies, SMA 18GHz

#### Ordering Information



Connector Options:  
SMA

Part Number Configurator			
Series, SMA	Connector 1	Connector 2	Length (in)
EM-B400SMA	XX	XX	-XXX

Connector 1		Connector 2	
SMA Male, Straight	MS	SMA Male, Straight	MS
SMA Male, Right Angle	MR	SMA Male, Right Angle	MR
SMA Female Bulkhead	FB	SMA Female Bulkhead	FB

\*\*\* - If Connector 1 = Connector, 2 omit Connector 2

#### Example:

EM-B400SMAMSMR-012, 12 inch cable with straight SMA male to right angle SMA male.

EM-B400SMAMS-024, 24 inch cable with straight SMA male both ends.

Contact us:  
sales@echelon-mw.com  
[www.echelon-mw.com](http://www.echelon-mw.com)  
770.742.8847